

# **EUROMULTI**

Multi-Function Cash Unit with Time Delay Lock



- ▼ The most effective security solution
- ✓ Ideal for banks, post offices, gas stations...
- Suitable for banknotes, coins, checks, cards, documents...
- ▼ Time delay for each drawer
- Unique modular system
- Silent alarm with smart blocking system
- PC connection
- ✓ ISO 9001

EuroMulti security units are designed for providing an increased cash security during working hours. They provide tested physical and psychological protection. Affordable price enables using them for each cashier. It provides different philosophy of security than expensive and heavy safes.

EuroMulti units consist of two main parts – steel box and drawer modules. The front panels of drawers are reinforced with 6 mm thick steel sheets. The drawers are based on modular system which provides hundreds of drawers and deposit slots combinations.


## **EuroMulti units are mainly used as:**


- Universal for cash deposit/dispense
- Cash deposit
- Cash exchange


#### What do EuroMulti units offer to you?


- Increasing security for your cashiers and valuables
- The most effective protection during working hours
- The best solutions for "open" banks


## The most popular drawer combinations:











EM R2R2P4R5

EM R2R2(R3-P4)R3

EM R2R2(R3-P4)(R3-P4)

EM R2R3P4R4

EM R2(R3-P4)(R3-P4)R2

#### **Features**

- Tested construction and grade A lock
- Modular system for drawers and deposit slots modules
- PIN access for 9 cashiers and 1 supervisor
- Time delay for each drawer from 0 to 99 sec/min
- Access for one/more cashier/s at the same time
- Protection between cashier-cashier and cashier-supervisor
- Silent alarm activation and blocking system
- Special automatic setting during robbery
- More than 25 special additional security settings
- Event history for 1000 events
- Alarm output NO/NC
- Internal UPC for min 100 openings
- RS232 and USB connection to PC
- ISO 9001 quality management





# Technical data

Time delay settings	1-999 sec. or 1-99 min. for each drawer
External blocking	yes
Serial ports	RS 232, USB and I2C
Number of drawers	2 - 5
Standard color	gray RAL 7035
Power supply	110 - 230/15V, 2A, CE
Reserve power supply	ACCU 12V/1,2 Ah
Dimensions (H × W × D)	690* × 500 × 530 mm, *hight adj. + (0 - 30 mm)
Weight	80 kg